

EAN	5 907 749 021 233	Product number	-
------------	-------------------	-----------------------	---

SECURA 6mm

Material	XPS
Description	
Insulating material for the acoustic use under floating floors	

Floating Floors

Technical Parameters					
EPLF		Value		Unit	Test Method
T	Thickness	6	+/- 5%	[mm]	PN-EN 823:2013
L	Length	790	+/- 5%	[mm]	PN-EN 822:2013
W	Width	590	+/- 5%	[mm]	PN-EN 822:2013
AW	Surface mass	0,192	+/- 5%	[kg/m ²]	EN ISO 23997:2012
QW	Density	32	+/- 5%	[kg/m ³]	PN-EN 1602:2013
RWS	Reflected walking sound	9	+/-2	[%]	EN 16205 CEN/TS 16354
IS	Impact sound improvement	22	+/-2	[dB]	EN ISO 10140
CS	Compressive strength at 0.5 mm compression	80	+/- 10%	[kPa]	EN ISO 3386 / EN826
CC	Static compressive strength			[kPa]	EN 1606
DL	Dynamic compressive strength	> 250 000		[cycles]	EN 13793
PC	punctual conformability	5	+/- 10%	[mm]	CEN TS 16354
TR	Thermal Resistance	0,19	+/- 0,003	[m ² K/W]	EN 12664
SD	sD-value			[m]	EN 12086
RLB	Resistance to Large Ball			[mm]	EN 438-2
RTF	reaction on fire				EN 13501-1

Logistic Parameters						
Packaging Unit	Form : Plete		Weight		Sizes	
	6	[m ²]	1,152 +/- 10%	[kg]	0	[mm x mm x mm]
Pallet	Pallet : 0		Weight		Sizes	
	120	[m ²]	23,04 +/- 10%	[kg]	0	[mm x mm x mm]

Packaging materials	Cardboard per item		Foil per item	
	0,000	[kg/item]	0	[kg/item]

Other		
Customs tariff number	Waste key	Recycling
68069000	170604	YES
Approvals		
AT-15-7785/2015		

The above information is based on current knowledge and the level of technological development. We do not claim to be exhaustive. All previous figures are invalid